

EF3000iS/iSEB

KEY FEATURES

Protection

Clean Power

Safe to use with sensitive equipment

CO Sensor

Engine shuts off if a high level of carbon monoxide is detected.

Ground Earth Terminal

Prevents Electric Shock

Power

30 Amp Outlet

30 Amp Outlet plug-in for more power

Dual 20A Outlets

More power for additional accessories

Yamaha Boost Technology

Senses when power is needed for start up of air conditioners, power tools, and other equipment.
(*iSEB Model)

Ease of Operation

Electric Start

Effortless turn the key to start (iSEB Model)

Fuel Gauge

Indicates amount of gasoline for refueling intervals

Noise Block Sound Reduction System

Very quiet 54.5-61 decibels

Reliability

SPECIFICATIONS

Type	Brushless Inverter
Peak AC Output (MAX)	3000 watts
Continuous AC Output (Rated)	2800 watts
Engine	OHV, air-cooled, single cylinder, 4-stroke
Displacement	171cc
LxWxH	26.8in x 17.5in x 21.8in
Dry Weight	156 lbs(iSEB)/136lbs(iS)
DC Output	12 amps @ 12 Volts
Fuel Tank Capacity	3.4 gal
Continuous Operation at 1/4 Rated Load	18.6 hrs
Noise Level (1/4 Load - Rated Load)	54.5 dBA
Warranty	3 Year Limited Warranty